



The **Protekt Slim series** in 1U Rack 19" format combines interactive technology with pure sine wave single-phase output in an ultra-compact design.

This solution is ideal for users requiring maximum energy protection and space optimization, with advanced monitoring options through USB HID ports and built-in management software.

Data Sheet

Reference	PH 7540	PH 7541
Power	750 VA / 450 W	1500 VA / 900 W
Input		
Rated Voltage	220 / 230 / 240 Vac	
Voltage Range	165 - 290 Vac	
Frequency	50 Hz / 60 Hz (Auto detection)	
Salida		
Voltage Regulation (Bat.)	220 - 240 Vac	
Frequency (Bat.)	50 Hz / 60 Hz ± 1%	
Waveform (Bat.)	Pure Sine	
Transfer time	4 ms	
Overload protection	Circuit breaker or internal protection fuse	
Battery		
Quantity / Tipe / n°	2x 6V/ 7 Ah	4x 6V / 9 Ah
Charging time (90%)	4 h	4 h
Indicators		
Led	Input current / Output	
Warning	Battery On / Battery Low / Overload / Fault	
Características		
433 x 44 x 230 (1U)	438 x 44 x 400 (1U)	438 x 44 x 389 (1U)
Weight (Kg)	8.6	16.2
Operating humidity	0 - 90 % without condensation	
Operating temperature	0 - 40°C	
<i>Specifications subject to change without notice. PHASAK® copyrights.</i>		