Callerreels

PHASAK's professional cable reels have a broad history in the market and years of experience in the professional and industrial sector.



Manufactured in Category 6 and 6A, the most popular categories that offer a more stable and reliable connection, being the favorite option for most installers for long distances. PHASAK coils guarantee compatibility with lower categories.

Bet on our certified 100% Copper model for complex and institutional installations or opt for the excellent performance and efficiency of CCA coils.





PHR 6100

PHASAK box of 305 meters of solid HTP ASVH 29 two rid cable in a box, category 6 in Phasak CCA. Supports transfer speeds up to 1 Gbps.



Data Sheet

Type: U/UTP

Category: Cat.6

Conductor material: CCA


AWG: 23AWG

Color: White

Length: 305M

EN 60332-1-2:04+A1:15+A11:16,

EN 60332-1-1:04+A1:15



PHR 6302 · CAT6 UTP 23AWG CCA		
Conductor	Material	99.99% Bare Copper Solid 23AWG; 1 / 0.565 ± 0.008
	Construction	23AWG; 1 / 0.565 ± 0.008 mm
Insulation	Material	Polyethylene
	Thickness	0.238±0.02 mm
	Diameter	1.05 ± 0.05 mm
Inner Layer	Direction	S(right)
	Pitch REF	30mm underneath
Outside Layer	Direction	S(right)
	Pitch REF	90±5mm
Cross	Material	Polyethylene
	Construction	4.4mm×4.4mm
Rip Cord	Material	Optional
Jacket	Material	PVC
	Thickness	0.50 mm(Min. Thichness: 0.45mm)
	Diameter	6.2 ± 0.20 mm
	Color	G-



