## Callerreels

PHASAK's professional cable reels have a broad history in the market and years of experience in the professional and industrial sector.



Manufactured in Category 6 and 6A, the most popular categories that offer a more stable and reliable connection, being the favorite option for most installers for long distances. PHASAK coils guarantee compatibility with lower categories.

Bet on our certified 100% Copper model for complex and institutional installations or opt for the excellent performance and efficiency of CCA coils.





## **PHR 6302**

Cable CCA · Cat 6 · UTP · AWG23 · Solid · 305m

PHASAK box of 305 meters of solid UTP LSZH network cable in a box, category 6 in Phasak CCA. Supports transfer speeds up to 1 Gbps.



## **Data Sheet**

Type: U/UTP

Category: Cat.6

Conductor material: CCA


AWG: 23AWG

Color: White

Length: 305M

EN 60332-1-2:04+A1:15+A11:16,

EN 60332-1-1:04+A1:15



PHR 6302 · CAT6 UTP 23AWG CCA		
Conductor	Material	99.99% Bare Copper Solid 23AWG; 1 / 0.565 ± 0.008
	Construction	23AWG; 1 / 0.565 ± 0.008 mm
Insulation	Material	Polyethylene
	Thickness	0.238±0.02 mm
	Diameter	1.05 ± 0.05 mm
Inner Layer	Direction	S(right)
	Pitch REF	30mm underneath
Outside Layer	Direction	S(right)
	Pitch REF	90±5mm
Cross	Material	Polyethylene
	Construction	4.4mm×4.4mm
Rip Cord	Material	Optional
Jacket	Material	PVC
	Thickness	0.50 mm(Min. Thichness: 0.45mm)
	Diameter	6.2 ± 0.20 mm
	Color	G-



