



The **Basic series** with interactive technology provides a basic level of security against voltage spikes, overload or short circuit to the connected devices. It has a cold start and will keep the devices connected to its 2 Schuko sockets protected.

Data Sheet

Reference	PH 9406	PH 9408
Power	600 VA / 360 W	800 VA / 480 W
Input		
Rated Voltage	220 / 230 / 240 Vac	220 / 230 / 240 Vac
Voltage Range	162 - 290 Vac	162 - 290 Vac
Frequency	50 Hz / 60 Hz (Auto detection)	50 Hz / 60 Hz (Auto detection)
Output		
Voltage Regulation (Bat.)	±10%	±10%
Frequency (Bat.)	50 Hz / 60 Hz ± 1%	50 Hz / 60 Hz ± 1%
Waveform (Bat.)	Pure sine	Pure sine
Battery		
Quantity / Tipe / n°	1x 12V / 7 Ah	1x 12V / 9 Ah
Indicators		
AC Mode	Green light	
Battery Mode	Green light (blink every 7 seconds)	
Characteristics		
Dimensions (WxHxD)	279 x 101 x 142	279 x 101 x 142
Weight (Kg)	4.2	4.9
Operating humidity	0 – 90 % without condensation	
Operating temperature	0 - 40°C	
<i>Specifications subject to change without notice. PHASAK® copyrights.</i>		