



PHASAK's **Ottima series** offers a simple, easy to install and affordable solution for small office or home environments. Equipped with interactive technology and 2 Schuko inputs, the Ottima series offers protection against surges, back-up in the event of power failures and autonomy for connected equipment.

Data Sheet

Referencia	PH 7266	PH 7288	PH 7210
Pwer	660 VA / 380 W	860 VA / 480 W	1060 VA / 600 W
Input			
Rated Voltage	220 / 230 / 240 Vac		
Voltage Range	162 - 290 Vac		
Frequency	50 Hz / 60 Hz (Auto detection)		
Salida			
Voltage Regulation (Bat.)	±10%		
Frequency (Bat.)	50 Hz / 60 Hz ± 1%		
Waveform (Bat.)	Simulated sinusoidal		
Transfer time	2 - 6 ms		
Overload protection	Circuit breaker or internal protection fuse		
Battery			
Quantity / Tipe / n°	1x 12V / 7 Ah	1x 12V / 9 Ah	1x 12V / 9 Ah
Charging time (90%)	8 h	8 h	8 h
Indicators			
Led	Power On / Battery use		
Warning	Battery On / Battery Low / Overload / Fault		
Características			
Dimensions (WxHxD)	96 x 138 x 286	96 x 138 x 286	96 x 138 x 286
Weight (Kg)	-	-	-
Operating humidity	0 - 90 % without condensation		
Operating temperature	0 - 40°C		
<i>Specifications subject to change without notice. PHASAK® copyrights.</i>			