



The **Protekt series** in 19" Rack format incorporates Pure Single-Phase sinusoidal interactive technology in a standardized format with a height of 2U.

A complete solution for users looking for maximum protection and advanced parameterization in time through the display and the built-in management software.

Data Sheet

Reference	PH 7512	PH 7521	PH 7530
Power	1260 VA / 720 W	2160 VA / 1400 W	3060 VA / 1800 W
Input			
Rated Voltage	220 / 230 / 240 Vac		
Voltage Range	165 - 290 Vac		
Frequency	50 Hz / 60 Hz (Auto detection)		
Salida			
Voltage Regulation (Bat.)	220 - 240 Vac		
Frequency (Bat.)	50 Hz / 60 Hz ± 1%		
Waveform (Bat.)	Pure Sine		
Transfer time	4 ms		
Overload protection	Circuit breaker or internal protection fuse		
Battery			
Quantity / Tipe / n°	2x 12V/ 7 Ah	2x 12V / 9 Ah	4x 12V / 9Ah
Charging time (90%)	4 h	4 h	4 h
Indicators			
Led	Input current / Output		
Warning	Battery On / Battery Low / Overload / Fault		
Características			
Dimensions (WxHxD)	438 x 88 x 400 (2U)	438 x 88 x 400 (2U)	438 x 88 x 400 (2U)
Weight (Kg)	14.2	16.5	22
Operating humidity	0 - 90 % without condensation		
Operating temperature	0 - 40°C		
<i>Specifications subject to change without notice. PHASAK® copyrights.</i>			