



The **Sirius series**, with automatic voltage regulation (AVR) and advanced parameterization, provides greater protection against voltage variations and spikes in the electrical network. It incorporates a complete display with information on the battery level, the connected load or the input and output voltages. The **Surge Protect** socket incorporated in all references allows the connection of equipment with high voltage peaks.

Data Sheet

Reference	PH 7312	PH 7315	PH 7322
Power	1260 VA / 720 W	1560 VA / 900 W	2260 VA / 1320 W
Input			
Rated Voltage	220 / 230 / 240 Vac		
Voltage Range	162 - 290 Vac		
Frequency	50 Hz / 60 Hz (Auto detection)		
Salida			
Voltage Regulation (Bat.)	220 - 240 Vac		
Frequency (Bat.)	50 Hz / 60 Hz ± 1%		
Waveform (Bat.)	Simulated sinusoidal		
Transfer time	4 ms		
Overload protection	Circuit breaker or internal protection fuse		
Battery			
Quantity / Tipe / n°	2x 12V / 7 Ah	2x 12V / 7.5 Ah	2x 12V / 9 Ah
Charging time (90%)	8 h	8 h	8 h
Indicators			
Led	Power On / Battery use		
Warning	Battery On / Battery Low / Overload / Fault		
Características			
Dimensions (WxHxD)	148 x 178 x 298	148 x 178 x 298	148 x 178 x 298
Weight (Kg)	8.7	9.1	10.8
Operating humidity	0 - 90 % without condensation		
Operating temperature	0 - 40°C		
<i>Specifications subject to change without notice. PHASAK® copyrights.</i>			