

Bobina de Cable Cobre 100% Sólido en caja · S/FTP  
 Bobina de Cabo 100% Cobre Sólido em caixa · S/FTP  
 100% Solid Copper Cable Reel in Box · S/FTP

EAN: 5605922050888



## Datos técnicos

**Tipo:** S-FTP LSZH

**Categoría:** Cat.6A

**Material conductor:** Cu

**Calibre:** AWG 23

**Color:** Gris

**Longitud de cable:** 305 M

## Fluke Test: Pass

EN 60332-1-2:2014+A11:2016,

EN 50288-9-1

## Dados técnicos

**Tipo:** S-FTP LSZH

**Categoría:** Cat.6A

**Material condutor:** Cu

**Calibre:** AWG 23

**Cor:** Cinza

**Comprimento do cabo:** 305 M

EN 60332-1-2:2014+A11:2016,

EN 50288-9-1

## Technical Data

**Type:** S-FTP LSZH

**Category:** Cat.6A

**Conductor material:** Cu

**AWG:** 24AWG

**Color:** Grey

**Length:** 305M

EN 60332-1-2:2014+A11:2016,

EN 50288-9-1

PHR 660 · CAT6A S-FTP LSZH 24AWG Cu		
Certification	Fluke Test	Pass
Characteristics	Conductive Material	Cu - Cooper
	Diameter	1.35 mm
	Shielding	S/FTP Sólido
	AWG	23
	Jacket Material	LSZH
	Length	305 M
	Cable Type	Round
	Specification	Cat.6A
Signal transmission	1 st	60um Al foil for each pair
	2 nd	96*0.12mm AL-MG braiding net
Twisted (Pairs 1, 2, 3, 4)	P1 - Blue/White-Blue	Twist Pitch: 16.84mm
	P2 - Orange/White-Orange	Twist Pitch: 8.95mm
	P3 - Green/White-Green	Twist Pitch: 10.6mm
	P4 - Brown/White-Brown	Twist Pitch: 15.16mm
Standards	Material	PVC jacket
	Thickness	0.7±0.01mm
	Diameter	8.0±0.5mm
	UNE/EN	EN 50288-9-1
	CPR	DIN EN 13501-6 Eca
	RoHs	2002/96/CE