



The **Protekt Slim series** in 1U Rack 19" format combines interactive technology with pure sine wave single-phase output in an ultra-compact design.

This solution is ideal for users requiring maximum energy protection and space optimization, with advanced monitoring options through USB HID ports and built-in management software.

## Data Sheet

| Reference                                                            | PH 7540                                     | PH 7541             |
|----------------------------------------------------------------------|---------------------------------------------|---------------------|
| Power                                                                | 750 VA / 450 W                              | 1500 VA / 900 W     |
| Input                                                                |                                             |                     |
| Rated Voltage                                                        | 220 / 230 / 240 Vac                         |                     |
| Voltage Range                                                        | 165 - 290 Vac                               |                     |
| Frequency                                                            | 50 Hz / 60 Hz (Auto detection)              |                     |
| Salida                                                               |                                             |                     |
| Voltage Regulation (Bat.)                                            | 220 - 240 Vac                               |                     |
| Frequency (Bat.)                                                     | 50 Hz / 60 Hz ± 1%                          |                     |
| Waveform (Bat.)                                                      | Pure Sine                                   |                     |
| Transfer time                                                        | 4 ms                                        |                     |
| Overload protection                                                  | Circuit breaker or internal protection fuse |                     |
| Battery                                                              |                                             |                     |
| Quantity / Tipe / n°                                                 | 2x 6V/ 7 Ah                                 | 4x 6V / 9 Ah        |
| Charging time (90%)                                                  | 4 h                                         | 4 h                 |
| Indicators                                                           |                                             |                     |
| Led                                                                  | Input current / Output                      |                     |
| Warning                                                              | Battery On / Battery Low / Overload / Fault |                     |
| Características                                                      |                                             |                     |
| Dimensions (WxHxD)                                                   | 438 x 44 x 400 (1U)                         | 438 x 44 x 400 (1U) |
| Weight (Kg)                                                          | 8.6                                         | 16.2                |
| Operating humidity                                                   | 0 – 90 % without condensation               |                     |
| Operating temperature                                                | 0 - 40°C                                    |                     |
| Specifications subject to change without notice. PHASAK® copyrights. |                                             |                     |